


CODE ZERO SUSPENDED | G3/P3



DE LED-Pendelleuchte. Direkt-indirekt oder rein direktstrahlend. Leuchtenkörper aus elliptisch geformtem Aluminiumprofil mit 60mm Lichtspurbreite. Erhältlich in 3 Größen, Proportionsverhältnis Länge zu Breite 2:1. Oberfläche weiß, silber, graphit, schwarz, champagner oder kupferfarben lackiert. Weitere Oberflächenoptionen siehe Lightnet-Surface-Collection oder RAL nach Wahl. Satinierter Opaldiffusor für Allgemeinbeleuchtung. Konverter in Leuchtgehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (1-10V, DALI, Touch-Dim, Casambi). Farbtemperaturen 2200K, 2700K, 3000K, 3500K, 4000K oder 6500K. Binning initial \leq MacAdam 3. Farbwiedergabe CRI>80 oder CRI>90. Stufenlos höhenverstellbare Parallel-Seilabhängung mit transparent ummantelter Zuleitung.


EN LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of elliptically shaped aluminium profile with 60mm width. Available in 3 sizes, ratio length to width 2:1. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Satin opal diffuser for general lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable parallel-cord suspension with transparent power supply cable.

FR Luminaire LED suspendu. Éclairage direct/indirect ou seulement direct. Corps du luminaire en forme d'ellipse parfaite en profilé d'aluminium de 60mm de large. Disponible en 3 dimensions, proportions parfaites de longueur pour largeur 2:1 Surface laquée blanc, argent, graphite, noir, champagne ou cuivre. Autres options de finition voir Lightnet-Surface-Collection ou RAL au choix. Diffuseur opale satinée pour un éclairage général. Driver intégré dans le luminaire, au choix ON/OFF ou graduable (1-10V, DALI, Touch-Dim, Casambi). Température de couleur 2200K, 2700K, 3000K, 3500K, 4000K ou 6500K. Binning initial \leq MacAdam 3. Rendu de couleur CRI>80 ou CRI>90. Filin parallèle droit et tendeur rapide réglable avec câble d'alimentation transparent.




PRODUCT-CODE: Z P3 O S D - 8 30 M - L1500 - K

PRODUCT FAMILY	- Z. Code Zero
TYPE	- P3 Direct-Indirect, G3 Direct-Only
OPTICAL SYSTEM	- O Opal
SURFACE FINISH	- W Snow White, V Ivory White,
	S Radiant Silver, U Urban Graphite, B Jet Black,
	H Champagne Silver, K Satin Copper
	- E On/Off, L DALI, D 1-10V, H Touch-Dim, C Casambi
CONTROL GEAR	U Separately Dimmable DALI
COLOUR REND.	- 8 CRI>80, 9 CRI>90, F Full Spectrum
COLOUR TEMP.	- 22 2200K, 27 2700K, 30 3000K, 35 3500K, 40 4000K, 65 6500K
POWER	- M Medium Power, H High Power
SIZE	- Luminaire Length in mm: L1500, L2000, L3000
SUSPENSION	- K Parallel Suspension
ON REQUEST	- Cable colour Red or Black




OPAL DIFFUSER / DIRECT-INDIRECT



DIRECT: ca.40% INDIRECT ca.60%

Length L [mm]	Lumen/Watt Medium Power	Lumen/Watt High Power
1500	17010lm/164W	20320lm/204W
2000	22390lm/218W	26830lm/272W
3000	32640lm/317W	39180lm/397W

OPAL DIFFUSER / DIRECT



DIRECT: 100%

Length L [mm]	Lumen/Watt Medium Power	Lumen/Watt High Power
1500	6630lm/88W	8600lm/117W
2000	9180lm/123W	11910lm/164W
3000	13770lm/182W	17860lm/242W

Lumen Values: Luminaire luminous flux at 4000K/CRI>80 / surface finished Snow White. Other configurations on request.

