

## Basic Déco A3/A4 | Surface



**DE** LED-Anbauleuchte für Wand- und Deckenmontage. Rein direktstrahlend. Leuchtenkörper aus Aluminiumprofil. Gehäuse-Außenfläche und Innendekor in unterschiedlichen Lackierungen und Kombinationen erhältlich, z.B. weiß, silber, graphit, schwarz, gold oder kupferfarben. Zu Oberflächenoptionen- und Kombinationen siehe Lightnet-Surface-Collection oder Bi-Colour-Auswahl. Rückversetzte Microprismenoptik mit optimierter Blendungsbegrenzung speziell für Office-Anwendungen. Satinierter Opaldiffusor für Allgemeinbeleuchtung mit max. Transmissionsgrad und homogener Lichtpunktauflösung. Konverter in Leuchtengehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (DALI, Touch-Dim, Casambi). Farbtemperatur 2200K, 2700K, 3000K, 3500K, 4000K, 6500K oder Tunable White (2700-6500K). Binning initial  $\leq$  MacAdam 3. Farbwiedergabe CRI > 80, CRI > 90 oder Full Spectrum. Auf Anfrage: Integration von Notlichtkomponenten.

**EN** LED surface-mounted luminaire for walls and ceilings. Direct only light distribution. Luminaire body made of aluminum profile. Outer housing and inner decor available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For further surface options see Lightnet-Surface-Collection or RAL of your choice. Recessed microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (DALI, Touch-Dim, Casambi). Colour temperature 2200K, 2700K, 3000K, 3500K, 4000K, 6500K or Tunable White (2700-6500K). Binning  $\leq$  MacAdam 3. Colour rendering CRI > 80, CRI > 90 or Full Spectrum. On request: Integration of emergency lighting components.

**B A3 A SL-8 30 M-D500-G**

Product Family	<b>B:</b> Basic
Type	<b>A3:</b> Direct only, <b>A4:</b> Direct only
Optical System	<b>A:</b> Microprismatic, <b>O:</b> Opal Diffuser
Surface Finish	<b>W:</b> Snow White, <b>V:</b> Ivory White, <b>S:</b> Radiant Silver, <b>U:</b> Urban Graphite, <b>B:</b> Jet Black, <b>H:</b> Anodic Champagne, <b>K:</b> Satin Copper
Control Gear	<b>E:</b> On/Off, <b>L:</b> DALI, <b>H:</b> Touch-Dim, <b>C:</b> Casambi, <b>6:</b> DALI DT6 for TW, <b>8:</b> DALI DT8 for TW
Colour Rendering	<b>8:</b> CRI>80, <b>9:</b> CRI>90, <b>F:</b> Full Spectrum [except 2200K]
Colour Temperature	<b>22:</b> 2200K, <b>27:</b> 2700K, <b>30:</b> 3000K, <b>35:</b> 3500K, <b>40:</b> 4000K, <b>65:</b> 6500K, <b>TW:</b> Tunable White 2700-6500K [D400-D1200]
Power	<b>E:</b> Low Power, <b>M:</b> Medium Power, <b>H:</b> High Power
Size	Luminaire Diameter in mm: <b>D300, D400, D500, D600, D800</b> [A3 only], <b>D900, D1200</b> [A4 only]
Reflector	<b>W:</b> Snow White, <b>V:</b> Ivory White, <b>S:</b> Radiant Silver, <b>U:</b> Urban Graphite, <b>B:</b> Jet Black, <b>H:</b> Anodic Champagne, <b>K:</b> Satin Copper, <b>G:</b> Satin Gold
On Request	Multisensor [D400-D800], Radar Sensor, Emergency Module [D400-D1200]



A3 Microprismatic   Direct			A3 Opal Diffuser   Direct			A4 Microprismatic   Direct			A4 Opal Diffuser   Direct		
D mm	Lumen/Watt Medium Power	Lumen/Watt High Power	D mm	Lumen/Watt Medium Power	Lumen/Watt High Power	D mm	Lumen/Watt Low Power	Lumen/Watt Medium Power	D mm	Lumen/Watt Low Power	Lumen/Watt Medium Power
300	830lm/8W	1430lm/13W	300	810lm/8W	1400lm/13W	300	880lm/8W	1730lm/14W	300	910lm/8W	1780lm/14W
400	1500lm/14W	2410lm/21W	400	1500lm/14W	2410lm/21W	400	1740lm/13W	3580lm/29W	400	1790lm/13W	3690lm/29W
500	2370lm/21W	3980lm/35W	500	2390lm/21W	4040lm/35W	500	2480lm/18W	4860lm/35W	500	2550lm/18W	5010lm/35W
600	3560lm/28W	5230lm/42W	600	3650lm/28W	5330lm/42W	600	3860lm/28W	7250lm/52W	600	3980lm/28W	7470lm/52W
800	5360lm/44W	6490lm/55W	800	5510lm/44W	6660lm/55W	900	6800lm/59W	11490lm/106W	900	7000lm/59W	11830lm/106W
						1200	11890lm/107W	20110lm/195W	1200	12250lm/107W	20700lm/195W

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.

