

Basic Visio Y9/X9 | Wall



DE LED-Anbauleuchte für Wand- oder Deckenmontage. Direkt- rundumstrahlend für dezente Wand- bzw. Deckenaufhellung oder direkt-indirektstrahlend stärkere indirekte Lichtkorona. Leuchtenkörper aus gegossenem Acryglas. Wahlweise Microprismenoptik mit optimierter Blendungsbegrenzung speziell für Office-Anwendungen oder satinierter Opaldiffusor für Allgemeinbeleuchtung mit max. Transmissionsgrad und homogener Lichtpunktauflösung. Distanzelement und Optikträger wahlweise weiß oder graphitfarben. Konverter in Leuchtengehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (DALI, Touch-Dim, Casambi). Farbtemperatur 2200K, 2700K, 3000K, 3500K, 4000K, 6500K oder Tunable White (2700-6500K). Binning initial \leq MacAdam 3. Farbwiedergabe $\text{CRI} > 80$, $\text{CRI} > 90$ oder Full Spectrum. Auf Anfrage: Integration von Notlichtkomponenten.


EN LED surface-mounted luminaire for walls or ceilings. Direct-omnidirectional light distribution for soft wall or ceiling illumination or direct-indirect light distribution for stronger indirect light distribution. Luminaire body made of cast acrylic glass. Available with microprismatic screen with optimized glare reduction especially for workplaces or satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Spacers and backplate optionally white or graphite coated. Driver integrated into luminaire housing, optionally switchable or dimmable (DALI, Touch-Dim, Casambi). Colour temperature 2200K, 2700K, 3000K, 3500K, 4000K, 6500K or Tunable White (2700-6500K). Binning \leq MacAdam 3. Colour rendering $\text{CRI} > 80$, $\text{CRI} > 90$ or Full Spectrum. On request: Integration of emergency lighting components.

B X9 O WE - 8 30 M-D300

- Product Family **B:** Basic
- Type **Y9:** Direct Only, **X9:** Direct-Indirect
- Optical System **A:** Microprismatic, **O:** Opal Diffuser
- Surface Finish **W:** Snow White, **U:** Urban Graphite
- Control Gear **E:** On/Off, **L:** DALI, **H:** Touch-Dim, **C:** Casambi, **6:** DALI DT6 for TW, **8:** DALI DT8 for TW
- Colour Rendering **8:** CRI>80, **9:** CRI>90, **F:** Full Spectrum [except 2200K]
- Colour Temperature **22:** 2200K, **27:** 2700K, **30:** 3000K, **35:** 3500K, **40:** 4000K, **65:** 6500K, **TW:** Tunable White 2700-6500K [D400-D610]
- Power **M:** Medium Power, **H:** High Power
- Size Luminaire Diameter in mm: **D300, D400, D500, D610**




Microprismatic | Direct-Indirect




| D mm | Lumen/Watt Medium Power | Lumen/Watt High Power |
|------|-------------------------|-----------------------|
| 300 | 760lm/6W | 1200lm/10W |
| 400 | 1770lm/14W | 3090lm/23W |
| 500 | 2840lm/21W | 5230lm/38W |
| 610 | 3830lm/28W | 7100lm/52W |

Microprismatic | Direct




| D mm | Lumen/Watt Medium Power | Lumen/Watt High Power |
|------|-------------------------|-----------------------|
| 300 | 630lm/5W | 1000lm/9W |
| 400 | 1630lm/13W | 2840lm/22W |
| 500 | 2470lm/19W | 4560lm/34W |
| 610 | 3340lm/25W | 6200lm/46W |

Opal Diffuser | Direct-Indirect



| D mm | Lumen/Watt Medium Power | Lumen/Watt High Power |
|------|-------------------------|-----------------------|
| 300 | 800lm/6W | 1260lm/10W |
| 400 | 1870lm/14W | 3270lm/23W |
| 500 | 2990lm/21W | 5500lm/38W |
| 610 | 4040lm/28W | 7470lm/52W |

Opal Diffuser | Direct



| D mm | Lumen/Watt Medium Power | Lumen/Watt High Power |
|------|-------------------------|-----------------------|
| 300 | 670lm/5W | 1060lm/9W |
| 400 | 1730lm/13W | 3020lm/22W |
| 500 | 2620lm/19W | 4830lm/34W |
| 610 | 3550lm/25W | 6570lm/46W |

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.



W Snow White



U Urban Graphite