

## Midpin G3 | Single Suspended



**DE** LED-Strahler für Pendelmontage. Direktstrahlend. Konverter in Leuchtgehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (DALI). Gehäuse aus Aluminium in weiß, silber, schwarz oder champagnerfarben lackiert. Weitere Oberflächenoptionen siehe Lightnet Surface Collection oder RAL nach Wahl. Farbtemperatur wahlweise 2700K, 3000K oder 4000K oder als Dim to Warm 3000K-1800K. Farbwiedergabe CRI>90. Binning initial  $\leq$  MacAdam 3. Austauschbare Linsenoptik mit Ausstrahlwinkel 30° (Medium) oder 40° (Flood). Optikring in verschiedenen Farbausführungen erhältlich. Zuleitungskabel wahlweise transparent, rot oder schwarz.

**EN** LED spotlight for pendant mounting. Direct only light distribution. Driver integrated into luminaire housing, optionally switchable or dimmable (DALI). Housing made of white, silver, black or champagne coated aluminum. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Colour temperature available as 2700K, 3000K or 4000K or as Dim to Warm 3000K-1800K. Colour rendering CRI>90. Binning  $\leq$  MacAdam 3. Changeable lens optics with beam angle 30° (medium) or 40° (flood). Optic ring available in different colour versions. Optionally transparent, red or black supply line.

**D G3 B B E - 9 27 M - G B**

Product Family	<b>D:</b> Midpin
Type	<b>G3:</b> Direct only
Lens Angle	<b>B:</b> Medium 30°, <b>C:</b> Flood 40°
Surface Finish	<b>W:</b> Snow White, <b>V:</b> Ivory White, <b>S:</b> Radiant Silver, <b>B:</b> Jet Black, <b>H:</b> Anodic Champagne
Control Gear	<b>E:</b> On/Off, <b>L:</b> DALI, <b>H:</b> Touch-Dim
Colour Rendering	<b>9:</b> CRI>90
Colour Temperature	<b>27:</b> 2700K, <b>30:</b> 3000K, <b>35:</b> 3500K, <b>40:</b> 4000K, <b>DW:</b> Dim to Warm 1800K-3000K [DALI only]
Power	<b>M:</b> Medium Power
Optic Ring	<b>W:</b> Snow White, <b>V:</b> Ivory White, <b>S:</b> Radiant Silver, <b>B:</b> Jet Black, <b>H:</b> Anodic Champagne, <b>G:</b> Satin Gold, <b>K:</b> Satin Copper
Cable Colour	<b>T:</b> Transparent, <b>R:</b> Red, <b>B:</b> Black



**Medium 30° Led Engine Eco, Medium Power**

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	2079/929	0.57 m
2 m	520/232	1.10 m
3 m	231/103	1.70 m
4 m	130/58	2.30 m

LED Engine	2700K	3000K	3500K	4000K
11W	610 lm	710 lm	750 lm	750 lm


**Flood 40° Led Engine Eco, Medium Power**

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	1454/591	0.77 m
2 m	364/148	1.50 m
3 m	162/66	2.30 m
4 m	91/37	3.10 m


LED Engine	2700K	3000K	3500K	4000K
11W	620 lm	730 lm	770 lm	770 lm




**B** Jet Black  
**W** Snow White




**B** Jet Black  
**A** Satin Silver




**B** Jet Black  
**B** Jet Black



**B** Jet Black  
**G** Satin Gold



**B** Jet Black  
**H** Anodic Champagne



**B** Jet Black  
**K** Satin Copper